

AMENDMENT TO THE CLAIMS

1. (Currently Amended) An attachment for a small loader having a frame and lift arms pivotally mounted to the frame, the lift arms having raisable and lowerable outer ends, comprising an attachment support, a first pivot for mounting the attachment support on at least portions of the loader lift arms to move therewith, at least one link attached to the attachment support and to other portions of the loader at second pivots, whereby relative movement between the lift arms and the other portions cause tilting of the attachment support about the first pivot to tilt the attachment support forwardly.

2. (Currently Amended) The attachment of claim 1, wherein the attachment comprises an open topped container and ~~the wherein the other portions of the loader comprises the loader frame, attachment support is supported on the first pivot to the lift arms,~~ the at least one link being connected to athe loader frame for causing tilting about the first pivot between the lift arms and the attachment support.

3. (Original) The attachment of claim 2, wherein the container is mounted for movement with outer ends of the lift arms, and the at least one link being pivotally mounted to the container and to the loader frame on the second pivots for causing the container to pivot relative to the lift arms on the first pivot as the lift arms move.

4. (Currently Amended) The attachment of claim 21, wherein the container is ~~pivotaly~~ on the attachment support and is mounted onto the lift arms with the attachment support, and a cylinder acting between the at least one link and the lift arms for causing pivotal movement of the attachment support and container about the first pivot to the lift arm.

5. (Original) The attachment of claim 1, wherein the attachment comprises a container on the support and having an open top, and the container being pivoted and dumped forwardly as it moves about the first pivot relative to the lift arms.

6. (Original) The attachment of claim 5, wherein said container comprises a cement mixer.

7. (Original) The attachment of claim 5, wherein said container comprises an auger mixer and has an open top, and a discharge trough at a forward end of the container.

8. (Original) The attachment of claim 1, wherein the attachment is selected from a group consisting of an auger mixer, a cement mixer, a hopper, and a sod roller, and the attachment is mounted on the support at a position on the lift arms rearwardly of forward ends of the lift arms to move the center of gravity of the attachment over at least portions of loader on which it is mounted.

9. (Currently Amended) A small loader comprising a frame adapted for movement over a supporting surface, the frame having at least one lift arm thereon that is pivotally mounted to the frame and has an outer forward end that is raisable and lowerable under power, an attachment on the at least one lift arm, said attachment being pivotally supported on the at least one lift arm adjacent the outer forward end, with the pivotal mounting to the rear of the outer forward end of the at least one lift arm to move the center of gravity of the attachment rearwardly of the outer forward end of the at least one lift arms with the at least one lift arm in a lowered position.

10. (Currently Amended) The loader of claim 9, wherein the at least one lift arm comprises a support at the outer forward end thereof, and a second working attachment mounted at the forward end of the at least one lift arm, in combination with the first mentioned attachment.

11. (Original) The loader of claim 9, wherein said attachment comprises one of a group of attachments including a cement mixer, an auger mixer, a sod roller, and an open top hopper.

12. (Currently Amended) The loader of claim 11, wherein the attachment is pivotally mounted to the at least one lift arm, and ~~wherein the at least one lift arm has a~~ tiltable plate pivotally mounted at the outer forward end of the at least one lift arm, a link connected between the attachment and the tiltable plate, and wherein tilting the tiltable plate causes pivoting of the attachment relative to the at least one lift arm.

13. (Currently Amended) The loader of claim 11, wherein ~~said attachment is pivotally mounted on at least one said lift arm,~~ there is ~~and a linkage connected between the attachment and the~~ frame of the loader whereby moving the at least one lift arm about a pivot relative to the frame causes the attachment to tilt relative to the at least one lift arm.

14. (Original) The loader of claim 9, wherein said attachment comprises a working body, and a support integral with the working body for pivotally mounting to portions of the at least one lift arm.

15. (Original) The loader of claim 9, wherein the only connections between the attachment and the frame is through the at least one lift arm, and whereby moving the at least one lift arm

raises and lowers the attachment without causing any change in relative position between the attachment and the at least one lift arm.

16. (Currently Amended) The loader of claim 9, wherein the at least one lift arm has a tilting attachment plate at the forward end thereof coupled to the attachment, a power operator connected between the at least one lift arm and the tilting attachment plate, and wherein there is a sensor for sensing movement of the at least one lift arm relative to the frame, said sensor causing ~~athe~~ power operator of the tilting attachment plate to change position to maintain the orientation of the attachment relative to a supporting surface as the at least one lift arm is raised and lowered.

17. (Currently Amended) The loader of claim 9, ~~wherein there is further comprising a locking linkage removably connected to the attachment and to the pivoting plate to prevent pivotal movement of the attachment relative to the at least one lift arm, and relative to a pivoting plate and a support for the attachment, the locking linkage being removable to permit rotating pivoting the attachment forwardly by pivoting the pivoting plate to a position where the attachment rests on the ground, and the pivoting plate can be disconnectable from the at least one lift arm.~~

18. (Currently Amended) The loader of claim ~~17~~9, ~~wherein there is further comprising a pivoting plate having a lower edge pivotally mounted at a plate pivot to the at least one lift arm, and being movable about the plate pivot, a first linkage connected between the attachment and the attachment pivoting plate, the first linkage causing pivoting of the attachment when an upper edge of the pivoting the attachment plate is rotated forwardly about the plate pivot. to dump contents of the hopper, the~~

~~attachment plate being pivotable to a position to rest on the ground to provide stability for the attachment with the lift arms in a lowered position, and the attachment is pivoted to a dumping position.~~

19. (Original) The loader of claim 9, wherein the attachment comprises a hopper and a stop bumper on a rear portion of the hopper aligned with a portion of the at least one lift arm to engage such portion and stop rearward pivotal movement of the hopper.

20. (Currently Amended) A mounting for a work attachment connectable to a loader arm which is moveable relative to a loader frame, the mounting comprising a support, a pivot mount on said support for pivotedal mounting to a loader arm, and a link mechanism pivotally connected to the support at one end, and the link mechanism having a second end adaptable to be pivotally mounted onto a portion of a loader frame having a loader arms for receiving the pivot mount, the portion of the loader frame and the pivot mount being movable relative to the pivot mount each other when the pivot mount is mounted on a loader arm of such frame.

21. (Original) The mounting of claim 20 including an attachment for containing material on the support.

22. (Currently Amended) The mounting of claim 20, wherein the pivot mount is positioned forwardly of a rear portion of the support, whereby portions of the support extend rearwardly from the pivot mount when mounted on a loader arm.

23. (Currently Amended) The mounting of claim 20, wherein the loader has a tilting attachment plate at forward ends of the lift loader arm, and an actuator for moving said tilting attachment

plate, the tilting attachment plate comprising the portion of the loader, the link mechanism being connectable to the tilting attachment plate for pivoting the support about a pivot axis of the pivot mount.

24. (Currently Amended) The mounting of claim 20, wherein the support mounts an open top receptacle, and the link mechanism controls pivotal movement of the open top receptacle on the pivot mounts ~~by movement of moveable members on the loader comprising the portion~~ to pivot the open top receptacle in a forward direction, and dump material from the receptacle over a forwardly extending end of the open top receptacle when mounted on a loader frame and when a loader arm on such loader frame is raised.

25. (Currently Amended) The mounting of claim 20, wherein the lift arms has an outer end that is ~~are~~ raiseable and lowerable, and said link mechanism is pivotally connected to at the portion of the loader ~~which frame and such portion~~ does not raise and lower with the ~~lift loader arms~~ on the loader frame.

26. (Currently Amended) The mounting of claim 23, wherein the ~~lift loader~~ arms has an outer end that is ~~are~~ raisable and lowerable, and said tilting attachment plate moves with said ~~lift loader arms~~, and the support has an attachment comprising an open top receptacle that is pivoted when the tilting attachment plate is tilted to cause the open top receptacle to dump over a forward end thereof.

27. (Original) The mounting of claim 22 further comprising a stop bumper on rear portion of the support, the stop bumper positioned to engage a portion of the loader on which the support is mounted to stop pivotal movement about the pivot mount in one direction of pivotal movement.